

APPLICATION FOR UNITED STATES LETTERS PATENT

of

James H. VanGilder
127 Shawnee Drive
Lake Kiowa, Texas 76240

for

TELECOMMUNICATIONS GRAPHICAL SERVICE PROGRAM


IP Administration
Legal Department, M/S 35
HEWLETT-PACKARD COMPANY
P.O. Box 272400
Fort Collins, CO 80527-2400

File No. 200314087-1

Certificate of Mailing Under 37 C.F.R. § 1.10

Express Mail Label No. ER452765725US Date of Deposit: October 30, 2003

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed to: Commissioner for Patents, BOX PATENT APPLICATION, P.O. Box 1450, Alexandria, VA 22313-1450.



TELECOMMUNICATIONS GRAPHICAL SERVICE PROGRAM

TECHNICAL FIELD

[001] The present invention relates generally to telecommunications networks, and
5 more specifically to software for providing desired services on such networks.

BACKGROUND OF THE INVENTION

[002] Modern telecommunications networks provide telephone users with a myriad
of features in addition to performing their primary function of placing calls between
10 users. Features such as call waiting, caller identification, and caller call back are
now standard features offered by most telephone service providers, and thus the
telecommunications networks of these service providers must be configured to
support these and other features such as handling calls from wireless users.

[003] **FIG. 1** is a functional block diagram of a conventional telecommunications
15 network **100** utilizing a global telecommunications standard known as "SS7," which
stands for "Common Channel Signaling System No. 7." The SS7 standard defines
protocols for defining how network elements in the public switched telephone
network (PSTN) communicate over digital communications networks to provide
wired and wireless call setup, routing, and control. The PSTN is the international
20 telephone system that utilizes copper wires and analog signals to represent voice
data and place calls between users, and the telephone service provided by this
system is known as plain old telephone service (POTS). Thus, the network **100**
utilizes network elements of the PSTN in addition to digital communications
networks to place calls and provide various advanced features to users.

25 [004] The network **100** includes service switching points (SSPs) **102** and **104** that
operate to originate or terminate calls between users, which are represented by
telephones **106**, **108**. Each SSP **102** and **104** communicates SS7 signaling
messages according to the SS7 standard to other SSPs in the network **100** to
setup, manage, and release voice circuits in the PSTN required to complete a call.
30 The network **100** further includes signal transfer points (STPs) **110**, **112** that route

SS7 signaling messages to an appropriate point in the network **100** based on routing information contained in the message. In this way, each STP **110**, **112** functions as a network hub and thereby eliminates the need for direct links between points in the network **100**. The network **100** further includes service control points (SCPs) **114** and **116**, each of which functions as a centralized database that determines how to route particular calls, such as calls having an **800** or **888** area code. In operation, one of the SSPs **102** and **104** originates a query message that is communicated to one of the SCPs **114** and **116**. In response to this query message, the SCP **114** and **116** receiving the query message communicates a response message to the originating SSP **102** and **104** that contains routing information associated the call.

[005] A number of service providers typically provide service through the network **100**, and these service providers are constantly trying to improve the performance of the network and to add new or enhance existing features for their customers. To make such modifications typically requires a service provider to modify software executing on various points in the network. The software executing on the SSPs **114** and **116** typically provides most of the advanced features offered by a service provider and supported by the network **100**, and thus a service provider must modify this software to add or change such features. On behalf of a service provider, a service developer **118** typically accesses computer systems (not shown) forming the SSPs **114** and **116** to modify the appropriate software and thereby modify the services executed by this software.

[006] Each service is a program on the SSP **114** and **116** that executes a particular service logic flow. While these service programs can be written in a variety of different languages, many are based upon a model known as the service independent building block (SIB) model, where SIB is a term defined by the International Telecommunication Union (ITU) Telecommunication Standardization Sector (ITU-T). With this model, an SIB is a unit of service logic that performs a simple function, such as playing an announcement or incrementing a counter, and programs are formed by interconnecting number of SIBs. Libraries of SIBs have

been defined, and the SIBs in these libraries are interconnected to form the desired service program and thereby provide the desired service. Associated with each SIB are inputs, outputs, and events, and the SIBs are interconnected using their events. For example, if there are three SIBs designated SIB1, SIB2, and SIB3, and SIB1
5 generates events A, B, and C, then SIB1 can be connected to SIB2 for event A and to SIB3 for events B and C.

[007] To modify an existing service the service developer **118** must modify the service logic flow defined by the interconnected SIBs forming the corresponding program. Similarly, to develop a new service the service developer **118** must
10 interconnect SIBs to perform the desired service logic flow. Current programs which may be utilized by the service developer **118** to implement desired modifications to an existing service or to develop a new service make the process difficult for a variety of reasons. First, current programs do not provide a sophisticated graphical user interface that allows the developer **118** to easily modify
15 existing and generate new service programs. Also, current programs do not provide the developer **118** with an easy way to reuse repeated service logic sub processes within a given service program and among other service programs. For example, a group of SIBs may be interconnected in the same way in several different locations within the same service program, and may be used a number of
20 different times in different service programs. The developer **118** must independently input this group of SIBs each time required, and test and debug each occurrence to ensure they have been input properly.

[008] Another issue that arises currently with the SIB model involves maintaining proprietary rights in service programs. The interconnected SIBs that collectively
25 form a service program are referred to as a service graph, and this service graph is akin to the source code of the service program. The service developer **118** may not be associated with the service provider and may be developing the service program for sale to a number of different service providers. In this situation, the service developer **118** ideally does not want to provide the service provider with access to
30 the service graph, which represents the key piece of intellectual property generated

and owned by the developer **118**. Current programs, however, do not provide the developer **118** with an easy way of downloading or "deploying" a developed service program onto the SCP **114** and **116** without providing the serviced provider access to the service graph.

- 5 [009] There is a need for a program and system for easily and efficiently designing and deploying service programs written using the SIB model.

SUMMARY OF THE INVENTION

[010] According to one aspect of the present invention, in a graphical user interface for a computer a method of displays objects for designing a service graph using a plurality of service independent building blocks. The method includes displaying a canvas object, displaying a toolbar object, displaying a menu object, and displaying a working folder tabs object that displays in one mode service independent building blocks that may be placed onto the canvas to design a service graph.

15

BRIEF DESCRIPTION OF THE DRAWINGS

[011] **FIG. 1** is a functional block diagram of a conventional telecommunications network using the SS7 standard.

20 [012] **FIG. 2** is a functional block diagram of a telecommunications service creation system including a graphical service design program for graphically defining service logic subroutines of repeated service logic sub processes according to one embodiment of the present invention.

[013] **FIG. 3** is a flow chart illustrating an overall process executed by the telecommunications service creation environment of **FIG. 1** in creating and deploying a telecommunications service in accordance with one embodiment of the present invention.

25 [014] **FIG. 4** is a functional block diagram of an example of a service graph generated by the graphical service design program of **FIG. 2**, where the service graph is a graphical representation of a telecommunications service executed by a

flexible service logic application program running on a server system of **FIG. 2** in accordance with one embodiment of the present invention.

[015] **FIG. 5** is a functional block diagram illustrating in more detail the components of a service independent building block of **FIG. 4** in accordance with one
5 embodiment of the present invention.

[016] **FIG. 6** is a diagram showing a display presented by the graphical service design program of **FIG. 2** for configuring a sample service independent building block.

[017] **FIG. 6** is a functional diagram showing the process through which service
10 independent building blocks set the values of call variables and thereby set the values of information elements contained in messages transmitted and received by the flexible service logic application program running on the server system of **FIG. 2** in accordance with one embodiment of the present invention.

[018] **FIG. 7** is a functional block diagram of a typical service graph including
15 several repeated service logic sub processes that may be implemented via respective subroutines generated by the graphical service design program of **FIG. 2** in accordance with one embodiment of the present invention.

[019] **FIG. 8** is a functional block diagram of a subroutine graph showing a generic
20 subroutine formed by a number of interconnected service independent building blocks according to one embodiment of the present invention.

[020] **FIG. 9** is an example subroutine graph of a ring back subroutine that determines if a number is a ring back number, as may be used in telephone system features such as calling back the last number that called you in accordance with one embodiment of the present invention.

[021] **FIG. 10** is a diagram showing a display presented by the graphical service
25 design program of **FIG. 2** for configuring the service independent building block in the subroutine graph of **FIG. 9** that looks up a phone number in a database table in accordance with one embodiment of the present invention.

[022] **FIG. 11** is a diagram showing a display presented by the graphical service design program of **FIG. 2** for configuring an example service independent building block in accordance with one embodiment of the present invention.

5 [023] **FIG. 12** shows a graphical design window displayed by the graphical interface program of **FIG. 2** according to one embodiment of the present invention.

[024] **FIG. 13** shows a graphical design window displayed by the graphical interface program of **FIG. 2** including working folder tabs and toolbars positioned in different locations within the window according to another embodiment of the present invention.

10 [025] **FIG. 14** shows a graphical design window displayed by the graphical interface program of **FIG. 2** including undocked or floating toolbars and working folder tabs according to a further embodiment of the present invention.

15 [026] **FIG. 15** is a functional block diagram illustrating a computer system corresponding to the client system of **FIG. 2** according to one embodiment of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[027] **FIG. 2** is a functional block diagram of a telecommunications service creation system **200** including a graphical service design program **202** for graphically
20 defining service logic subroutines corresponding to repeated service logic sub processes according to one embodiment of the present invention. The graphical service design program **202** enables a service developer to easily develop a service logic subroutine graph using a graphical interface, where a service logic subroutine graph corresponds to a number of service independent building blocks (SIBs)
25 interconnected to execute a repeatedly used service logic sub process. For example, within a single telecommunications service program an error handling subroutine may be used in a number of different places and thus would be well suited to being implemented via a subroutine. Another example of a subroutine that may be used in multiple service programs, and thus in multiple services, is a

subroutine for validating and loading account information from a service database. In this way, the graphical service design program **202** requires only one subroutine graph be developed and then inserted via a corresponding subroutine icon into a single service graph or into multiple service graphs in as many places as required.

5 This makes developing service programs faster and results in more reliable programs, which lowers the overall cost of developing new service programs. The graphical service design program **202** also provides for easy deployment of a newly developed service program without requiring that a service provider be provided access to the service graph for the service program.

10 [028] In the following description, certain details are set forth in conjunction with the described embodiments of the present invention to provide a sufficient understanding of the invention. One skilled in the art will appreciate, however, that the invention may be practiced without these particular details. Furthermore, one skilled in the art will appreciate that the example embodiments described below do
15 not limit the scope of the present invention, and will also understand that various modifications, equivalents, and combinations of the disclosed embodiments are within the scope of the present invention. Embodiments including fewer than all the components of any of the described embodiment are also within the scope of the present invention. Finally, the operation of well known operations has not been
20 shown or described in detail below to avoid unnecessarily obscuring the present invention.

[029] In the telecommunications service creation system **200**, the graphical service design program **202** executes on a client system **204**, which is typically a personal computer. The graphical service design program **202** includes a graphical interface
25 **206** that allows a service developer to design new telecommunications services by selecting desired SIBs from an SIB library **208**, placing the selected SIBs onto a work area or "canvas," and then interconnecting the selected SIBs as required to perform a desired service logic process and to thereby create a service graph **207**, as will be described in more detail below. The service graph **207** is a graphical
30 representation of a telecommunication service, and is then processed and

transferred to a server system **218** on which a flexible service logic (FSL) program **226** executes the processed service graph to thereby provide the underlying service, as will also be explained in more detail below. The SIB library **208** includes a number a standard SIBs that may be utilized by the developer in generating the service graph, with several standard libraries of SIBs being available, such as CAMEL-3-CSCC (CAP), CAMEL-3-MAP, CS1, ETSI INAP, and TTNS SIB libraries, each of which will be familiar to those skilled in the art.

[030] The graphical service design program **202** further includes service graph and subroutine graph files **210**, which correspond to graphs created and saved using the program. Each service created using the program **202** has associated service data tables **212** that are utilized to store such information as, for example, subscriber information. During execution of the service, the SIBs forming the service graph **207** read data from and write data to these service data tables **212**. A message definition or "message set" **214** is also part of the graphical service design program **202**, and is a collection of transaction capabilities applications part (TCAP) messages utilized in an SS7 system as previously described in **FIG. 1**. Communications between service switching points (SSPs) **102** and **104** (**FIG. 1**) and service control points (SCPs) **114** and **116** (**FIG. 1**) occur through TCAP messages. For example, the SSP **102** may send a TCAP message to the SCP **114** to determine a routing number associated with a dialed 800/888 number and to check a personal identification number of a calling card user. Each message in the message set **214** includes a number of fields or information elements IEL and the SIBs forming the service graph **207** utilize call variables CV to write data to and read data from these information elements, as will be described in more detail below. Briefly, the message set **214** defines information elements IEL that make up each message in the message set, and a group of call variables CV are associated with these information elements and are available for use with the service graph **207**, with each call variable CV being associated with a corresponding information element. This will be described in more detail below with reference to **FIG. 6**.

[031] The telecommunications service creation system **200** further includes a deployment program **216** contained on the client system **204**. The deployment program **216** processes the service graph **207** created using the graphical interface program **206** to create files suitable for transfer to a server system **218**, which
5 executes these files to thereby provide the underlying telecommunications service. More specifically, once a service graph **207** has been generated with the graphical interface program **206**, the service graph is "deployed" or "cutover" to the server system **218** using the deployment program **216**. The service developer controls the interface program **206** to generate exported files **220** from the service graph **207**,
10 where the exported files include a service script along with other files necessary for deployment of the service graph. The deployment program **216** uses only the exported files **220**, which may be useful when deploying the same service to multiple server systems **218** or when providing services to service providers without actually supplying the developed service graphs **207** to such service providers. In
15 this way, the deployment program **216** provides a convenient and secure way for a service developer to design a service and to thereafter distribute the files corresponding to the designed service to customers without disclosing proprietary intellectual property contained in the service graph **208**. The development program **216** also provides a convenient and secure way for the developer to deploy the
20 service on the server system **218**. The interface program **206** may also directly cut over the service graph **207** to the server system **218** without using the deployment program **216**.

[032] A provisioning program **222** on the client system **204** is used to add data to service data tables contained on the server system **218** and which are created
25 according to the service data table definitions **212** utilized by the service graph **207**. Also contained on the client system **204** is an application builder program **224**, which is used to generate the FSL application program **226**, which, as previously mentioned, is an executable program that runs on the server system **218** to execute the underlying telecommunications service. The application builder program **224**

allows a service developer to generate, from the client system **204**, the FSL application program **226** that is to run on the server system **218**.

[033] On the server system **218**, a build server **228** operates to perform several functions. First, the build server **228** operates in conjunction with the application
5 builder **224** to generate the FSL application program **226**. More specifically, the application builder **224** is used to select particular SIB libraries **208**, and the application builder then communicates with the builder server **228** to bind an application framework (not shown) residing on the server system **218** with the selected SIB libraries to generate the FSL application program **226**, as indicated by
10 an arrow **230** in **FIG. 2**. The server system **218** runs on an SCP **114** and **116** in the SS7 network **100** in **FIG. 1**, and the application program **226** communicates with other points (not shown) in the network through TCAP messages, as indicated in **FIG. 2**. The service image **232** communicates with the application program **226** through call variables CV to set the value of a corresponding information element in
15 a TCAP message, as will be discussed in more detail below.

[034] The build server **228** also operates to communicate with either the graphical interface program **206** or the deployment program **216** to compile the service script received from either of these two programs. During deployment of the service graph **207**, either the graphical interface program **206** or the deployment program
20 **216** communicates with the build server **228** and transfers the service script corresponding to the service graph **207** to the build server. The build server **228** compiles the received service script to thereby generate a corresponding service image **232** that is stored in a service image database **234** on the server system **218**. To execute the underlying service, the FSL application **226** executes the service
25 image **232**, as indicated by the dotted lines showing the service image in the application program.

[035] The server system **218** further includes an open database server **236** that operates, during cutover of the service graph **207**, to create any service data tables required for the associated service and stores these service data tables in a service
30 data table database **238**. Once these service data tables are created and stored in

the service data table database **238** on the server system **218**, the provisioning program **222** communicates with the open database server **236** to insert data into these tables. The provisioning program **222** can also be used to independently create the required service data tables and store these tables in the database **238** prior to cutover.

[036] The overall process executed by the telecommunications service creation system **200** in creating and deploying a telecommunications service will now be described in more detail with reference to **FIG. 2** and to the flow chart of **FIG. 3**. The process starts in step **300** and proceeds immediately to step **302** in which the graphical interface program **206** is utilized to develop the service graph **207** corresponding to the desired telecommunications service. As previously mentioned, to create the service graph **207** a service developer selects appropriate SIBs from the SIB library **208**, places them on a screen or canvas displayed by the program, and interconnects the SIBs as required to execute the desired service logic process.

[037] Once the service graph **207** is created in step **302**, the FSL application program **226**, in step **304**, is created on the server system **218** using the application builder **224** and build server **228**. After the FSL application program **226** has been created in step **306**, the service graph **207** created in step **302** is cut over or deployed either directly using the graphical interface **206** or using the deployment program **216**. During the deployment process, the build server **228** receives a service script corresponding to the developed service graph **207** and compiles the received service script to generate the corresponding service image **232**, which is stored in the service image database **234** on the server system **218**.

[038] In step **308** the service data table database **238** on the server system **218** is created using the provisioning program **222** on the client system **222** and the open database server **236** on the server system. The provisioning program **222** communicates with the open database server **236** to insert data into the service data tables after deployment of the service graph **207** in step **306**. Alternatively, the provisioning program **222** can also be used to independently create the required

service data tables and store these tables in the database **238** prior to deployment of the service graph **207**, in which case step **308** would occur prior to step **306**.

[039] The process goes to step **310** and the FSL application program **226** executes the service image **232** to thereby execute the designed service. During execution of the service, the FSL application program **226** and service image **232** communicate via call variables CV to transfer values contained in the TCAP messages sent and received by the FSL application program. Those skilled in the art will appreciate that the particular order in which the steps of the process of **FIG. 3** are executed may vary.

[040] **FIG. 4** is an example of the service graph **207** and shows a number of SIBs interconnected to form a desired service logic process. Each time an SIB is placed on the canvas an "instance" of that SIB is created and is represented in the service graph **207** by a corresponding icon. In the present description, the term "SIB" as used herein is used to refer to the function performed by the SIB or to the icon representing the SIB, or both.

[041] In the example of **FIG. 4**, a start SIB **400** indicates the start of the service logic process and a sample SIB designated SIB1 is coupled to the start SIB **400** through a link **402**. The SIB1 is also coupled through a link **404** to a second sample SIB designated SIB2 and to a subroutine **406** represented by a corresponding icon. An end SIB **408** is linked to SIB2 through a link **410** and a third sample SIB designated SIB3 and another end SIB **412** are coupled in series through respective links **414**, **416** to the subroutine **406** as shown. The subroutine **406** is a group of SIBs (not shown) that execute a desired service logic sub process that is repeatedly used within a give service logic process or among different service logic processes, as will be described in more detail below.

[042] **FIG. 5** is a functional block diagram illustrating in more detail the components of a typical SIB **500** corresponding to any of the SIB1-SIB3 of **FIG. 4**. The SIB **500** includes inputs **502** that are applied to SIB logic that executes the simple function of the SIB, where each input is assigned to a corresponding call variable. As previously mentioned, call variables CV are used in communicating information

between the service corresponding to the service graph **207** and TCAP messages being communicated by the FSL application program **226**. The SIB **500** further includes outputs **506**, each of which is also assigned to a corresponding call variable. Finally, the SIB **500** includes events, which are parameters that are
5 communicated from one SIB to another via links and which control the logic flow within the service graph **207**. For example, in **FIG. 4** the link **404** defines events that are communicated to SIB2 and to the subroutine **406**, and the values of these events may, for example, determine whether the subroutine executes to perform a first function or whether the SIB2 executes to perform a second function.

10 [043] **FIG. 6** is a functional diagram showing the process through which SIBs set the values of call variables CV which, in turn, set the values of information elements IEL contained in TCAP messages transmitted and received by the FSL application program **226**. In the example of **FIG. 6**, an SIB **600** has two outputs and each output is assigned to a respective call variable CV1, CV2. To set the value of an
15 information element IEL in a TCAP message, the SIB **600** sets the values of the call variables CV1, CV2. As previously mentioned, the service image **232**, which is a compiled version of the service graph **207** containing the SIB **600**, communicates with the FSL application program **226** through call variables CV. In response to the call variables CV1, CV2, the FSL application **226** modifies the information elements
20 IEL in the appropriate message in the message set **214** associated with the underlying service. In **FIG. 6**, the message set **214** is shown as including a number of individual messages MSG1-MSGN, each message including a number of information elements IEL. The call variables CV1 and CV2 are associated with information elements IEL1 and IEL2 in the message MSG2, and the SIB **600** sets
25 the values of these information elements through the process variables CV1 and CV2.

[044] **FIG. 7** is a functional block diagram of a typical service graph **700** including several groups **702-706** of SIBs, each group of SIBs being a repeated service logic sub process that may be implemented via a respective subroutine generated by the
30 graphical service design program **202**. The group **702** could, for example, be a

group of SIBs that execute an error handling routine used in multiple instances within the single service graph **700**. This error handling routine is well suited to being implemented through a subroutine. The group **704** could, for example, be a group of SIBs that execute a routine to validate and load account information from the service database **238 (FIG. 2)**. This is routine may be used in a number of different service graphs **700**, and thus is similarly well suited to being implemented through a subroutine.

[045] The graphical interface program **206** creates subroutines in much the same way as creating the service graph **700** corresponding to an overall service process. Thus, to create a subroutine the graphical interface program **206** is used to create a subroutine graph, an example of which is shown as a subroutine graph **800** in **FIG. 8**. The SIBs contained in the subroutine graph **800** can be selected and inserted as previously described for the service graph **207** of **FIG. 4**, or can be copied from portions of other service graphs. In a service graph, each subroutine is represented with a distinct icon designated the call subroutine icon, an example of which is shown for the subroutine **406** in **FIG. 4**.

[046] The subroutine graph **800** represents a service logic sub process that is then called by the service graph **207** or **700**. In the following description, the only the example service graph **207** will be referred to for ease of explanation. The graphical interface program **206** is used to create the subroutine graph **800** in much the same way as the service graph **207** would be created. A new subroutine is selected to open a new subroutine canvas, and SIBs are then selected and placed on the canvas to create particular instances of such SIBs. These SIBs are thereafter interconnected through links as required to perform the desired service logic sub process. Each subroutine graph **800** includes special SIBs associated only with subroutine graphs, namely a begin subroutine SIB **802** that indicates the start of a subroutine graph and one or more return SIBs **804, 806** indicating the end of a particular logic flow within the subroutine graph where control is returned to the service graph **207** calling the subroutine graph. In addition to the begin subroutine SIB **802** and return SIBs **804, 806**, the SIBs required to perform the desired service

logic sub process are also inserted into the subroutine graph **800** and are designated SIB1-SIB4 and interconnected as shown in this example.

[047] In addition to creating instances of the required SIBs, the graphical interface program **206** is also used to define a name, inputs, outputs, and events for the
5 subroutine graph **800**. Note that the terms subroutine and subroutine graph may be used interchangeably herein. The name assigned to the subroutine graph **800** is displayed in the corresponding icon shown in the service graph **207**. The inputs are any inputs to the subroutine graph **800** that may be set by the calling service graph **207**, while the outputs are parameters that are returned to the calling service graph.
10 Similarly, events of a subroutine graph **800** are the events that can be returned to the calling service graph **207**, and are returned to the calling service graph by the return SIBs **804**, **806**. Each return SIB **804**, **806** has no output events of its own, but instead returns one of the events defined for the subroutine graph **800**. Where there is more than one return SIB **804**, **806**, as is obviously the case in the graph
15 **800**, each return SIB can return the same or a different event.

[048] Once a subroutine graph **800** is defined using the graphical interface program **206**, the program displays a call subroutine SIB or icon that allows a developer to create instances of the subroutine where desired in service graphs **207**. As previously mentioned, an example of a call subroutine SIB is shown for the
20 subroutine **406** of **FIG. 4**. Instances of the subroutine may thus be created, for example, by clicking on the corresponding icon displayed on a working tab panel displayed by the program **206** and then dragging the icon to the canvas displayed by the program.

[049] In one embodiment of the program **202**, the graphical interface program **206**
25 allows the subroutine graph **800** to be called from multiple service graphs **207** and also to be called from other subroutine graphs, but does not allow a subroutine graph to be called recursively (i.e., a subroutine graph cannot call itself) and also does not allow a subroutine graph called by another subroutine graph to call that original subroutine graph (i.e., if subroutine A calls subroutine B, then subroutine B
30 cannot call subroutine A).

- [050] In this way, the graphical service design program **202** requires only one subroutine graph **800** be developed and then inserted via a corresponding subroutine icon into a single service graph **207** or into multiple service graphs in as many places as required. Telecommunications services may therefore be developed faster using the program **202**. Moreover, the use of subroutine graphs **800** will make new services more reliable since once a subroutine graph is designed and validated as operating properly, the service logic sub process executed by the subroutine graph will not again need to be checked when validating an overall service graph containing the subroutine.
- [051] **FIG. 9** is an example subroutine graph **900** of a ring back subroutine that determines if a number is a ring back number, as may be used in telephone system features such as calling back the last number that initiated the call and which is commonly known as the “*69” feature. The subroutine graph **900** includes a begin subroutine SIB **902** which is linked to a read ring back SIB **904**. The read ring back SIB **904** determines whether the number is a call back number, and provides a ring back indicator having a value indicating the results of this determination. If the SIB **904** determines the number is a ring back number, then the SIB sets the ring back indicator value to true and in response to this true indicator an “is ring back” SIB **906** sets a true “is ring back” event. A return SIB **908** returns the true “is ring back” event to the calling service graph (not shown). If the SIB **904** determines the number is not a ring back number, then the SIB sets the ring back indicator value to false and in response to this false indicator an “is not ring back” SIB **910** sets a true “is not ring back” event. A return SIB **912** returns the true “is not ring back” event to the calling service graph (not shown).
- [052] **FIG. 10** is a diagram showing a display **1000** presented by the graphical interface program **206** of **FIG. 2** for the read ring back SIB **904** of **FIG. 9**. The display **904** allows a service developer to configure the SIB **904** as required. The display shows the SIB **904** uses a control variable “ringBackNumber” to determine whether a number is a call back number.

[053] FIG. 11 is a diagram showing a display 1100 presented by the graphical interface program 206 of FIG. 2 for an example "PlayAnnouncement" SIB. The display 1100 shows the input and output parameters associated with the SIB. Each input parameter is indicated as being required or optional through an associated "R" or "O" in the far left column for the parameter, and values for the required input parameters are indicated. Three output parameters are shown and an appropriate call variable CV may be assigned to each, although in the display no such call variables are shown as being assigned.

[054] FIG. 12 shows a graphical design window 1200 displayed by the graphical interface program 206 of FIG. 2 for generating the service graph 207 according to one embodiment of the present invention. The graphical design window 1200 is part of a graphical user interface of the interface program 206 through which a service developer provides inputs to develop the service graph 207. The graphical design window 1200 includes a canvas portion or object 1202 in which the developer places SIBs and subroutines and interconnects these icons to form the service graph 207. A number of SIBs are shown in the canvas object 120 in the example of FIG. 12.

[055] The graphical design window 1200 further includes a working folder tabs object 1204 positioned to the left of the canvas object 1202. The working folder tabs object 1204 includes an SIB button or pane 1206, a services pane 1208, a service data tables pane 1210, and a messages pane 1212 which determine the content displayed by the working folder tabs object. When the SIB pane 1206 is selected by clicking on the pane, the working folder tabs object 1204 displays the currently available SIB libraries and the SIBs in each library, as shown in FIG. 12. When the services pane 1208 is selected, the working folder tabs object 1204 displays icons representing the service graphs 207 and icons representing the subroutine graphs 800. The developer may then select a graph 207 or 800 to open the graph, meaning the graph is displayed in the canvas object 1202 to be viewed and/or modified by the developer. Selecting the service data tables pane 1210 causes the working folder tabs object 1204 to display any service data tables 212

currently available for use by the developer. Finally, when the messages pane **1212** is selected the working folder tabs object **1204** displays icons representing the message sets **214** (**FIG. 6**) currently available for use as well as the messages MSG in each message set.

- 5 [056] The graphical design window **1200** further includes a menu object **1214** that allows the developer to select from among several familiar menus including a “file” menu, “edit” menu, “view” menu, and “tools” menu. Below the menu object **1214** in the embodiment of **FIG. 12** is toolbars object **1216** that may include several different toolbars. The toolbars object **1216** may include a standard toolbar corresponding to
10 the first nine buttons starting from the leftmost button in the toolbar object **1216**. The service developer uses the standard toolbar to perform basic operations such as opening an saving files. A graph toolbar may also be included in the toolbars object **1216**, and corresponds to the remaining buttons shown for this object in **FIG. 12**. The graph toolbar is used to perform the most common operations performed
15 in developing a service graph **207**, such as linking SIBs and selecting instances of SIBs in the canvas object **1202**. The toolbars object **1216** may include other toolbars as well, such as an alignment toolbar used to align selected SIBs, a space and nudge toolbar used to arrange SIBs in the canvas object **1202**, or a zoom and pan toolbar used to change the view of the canvas object.
- 20 [057] The toolbar object **1216** along with the various toolbars that may be included in that object may be positioned in different locations within the graphical design window **1200**, as may the working folder tabs object **1204** and canvas object **1202**. The sizes of each of these objects **1202**, **1204** and **1216** may also be varied. **FIG. 13** shows a graphical design window **1300** displayed by the graphical interface
25 program **206** including a canvas object **1302**, working folder tabs object **1304**, and toolbars object **1306** including a standard toolbar **1308** positioned above the canvas object and a graph toolbar **1310** positioned between the canvas object and working folder tabs object according to another embodiment of the present invention. In the embodiment of **FIG. 13**, each toolbar **1308**, **1310** is displayed in a large button

mode in which a short label in addition to an icon is displayed for each of the button in the toolbars.

[058] FIG. 14 shows a graphical design window **1400** displayed by the graphical interface program **206** of FIG. 2 including a canvas object **1402** and an undocked or floating working folder tabs object **1404**, along with a toolbar object **1406** including a floating graph toolbar **1408** and an undocked or fixed standard toolbar **1410**. The standard toolbar **1410** as well as the working folder tabs object **1304** and toolbars **1308** and **1310** of FIG. 13 are said to be fixed or "docked" because they are in a fixed position relative to the associated canvas objects **1302** and **1402**. In contrast, the working folder tabs object **1404** and graph toolbar **1408** are referred to as being undocked or floating since they may be moved around to different locations relative to the canvas object **1402**. The floating working folder tabs object **1404** and toolbar **1408** always remain in front of the graphical design window **1400** so that they are not hidden behind this window.

[059] FIG. 15 is a functional block diagram of a computer system **1500** corresponding to the client system **204** of FIG. 2 according to one embodiment of the present invention. The computer system **1500** includes a processor **1502** for performing various computing functions and for executing the graphical service design program **202** and associated programs **216**, **222** and **224**, as well as for executing other software to perform specific calculations or tasks. In addition, the computer system **1500** includes one or more input devices **1504**, such as a keyboard or a mouse, coupled to the processor **1502** to allow an operator to interface with the computer system. Typically, the computer system **1500** also includes one or more output devices **1506** coupled to the processor **1502**, such as a printer and a video display or monitor. One or more data storage devices **1508** are also typically coupled to the processor **1502** to store data or retrieve data from external storage media (not shown). Examples of typical storage devices **1508** include hard and floppy disks, tape cassettes, compact disk read-only (CD-ROMs) and compact disk read-write (CD-RW) memories, and digital video disks (DVDs).

[060] One skilled in the art will understand that even though various embodiments and advantages of the present invention have been set forth in the foregoing description, the above disclosure is illustrative only, and changes may be made in detail, and yet remain within the broad principles of the invention. For example, the
5 sequence of operations in the various processes described above may be varied, and the client and server computer systems may each be contained on a single computer or on a network of suitably connected computers, and also may be contained on a variety of different types of computer systems running a variety of different operation systems. Moreover, concepts and principles of the present
10 invention may be applied to other types of telecommunications systems. Therefore, the present invention is to be limited only by the appended claims.